## RED200 RX130 Elevator Ø 300 mm - 3048 mm

For inspections with pipe diameters of more than DN 300 up to DN 3048mm your ROVION system can be upgraded with an optional elevator. This elevator can automatically be moved up or down though the control panel thus offering perfect centering of the camera unit inside the pipingsystem in each and every inspection situation.

## **Technical data - RED200**

Normal pipe widths	DN 300 up to DN 3048
Pressure tightness	Up to maximum 1 bar
Internal pressure sensor	Yes
Drive	Electronic lift
Optional accessories	Auxiliary lights RAL130, RAL200, RAL1000-RCX90, RAL1000-DSIII, camera RCX90, Fisheye camera DSIII, PTP70II, PTC50, RAC50
Power supply	Through cable reel
Optional accessories	• / / /
Protection class	IP68 up to 10 m of water depth
Ambient temperature range	0°C to 40°C
Storage temperature range	-20°C to 70°C
Material	Aluminum (anodized), stainless steel
Dimensions (WxHxD)	Retracted: 80 x 145 x 315 mm Extended: 80 x 320 x 315 mm
Weight	approx 3.2 kg



- Simple and fast mounting to/removal from the crawler
- Motor-driven
- Stepless Hight adjustment
- Interface for cameras and auxiliary lights
- Exclusively compatible to the RX130 crawler
- Optionally available as EX version